



designed for scientists



## RV 10 digital FLEX

/// Hoja de Datos

The RV 10 digital represents the continual enhancement of the IKA RV 10 rotary evaporator line. The unit comes with an universal heating bath, state-of-the-art safety features and digital connectivity. The RV 10 digital is a robust and reliable lab companion. Its optimized bath volume allows for fast heat-up times. That's why the RV 10 basic delivers reliable and reproducible process results that are usually reserved for more costly systems. Additional features such as smooth start, left-right interval or timer function capability support the user in their daily lab work. Another important aspect of the RV 10 digital are the sophisticated safety features. The motorized lift has an automated lift-out function in case of power outage to prevent superheating of the solvent. Safety temperature circuits can be set individually. Dry-run protection, adjustable lower end stop and lock function of bath setting complete the line of safety features. Furthermore, IKA offers



designed for scientists

a choice of coated glassware for increased safety needs. The RS 232 interface allows for remote control via IKAs “labworldsoft”. The Heating bath is controlled via the IR interface from the main unit.

- 4 liter heating bath
- Universal water/oil heating bath
- Motorized lift with “safety-stop” function
- RS 232 and IR Interface
- Optimized heating bath volume for fast heat-up
- Ergonomically placed handles on heating bath
- Smooth start
- Left-right interval
- Timer function
- Dry-run protection
- Safety temperature circuits
- Lower-end stop
- Choice of coated or uncoated glassware
- Push-off mechanism to loosen tight fitted glassware
- Easy and safe operation due to ergonomical design of the user interface



## Información Técnica

Tipo de enfriamiento	sin condensador
Principio del motor	DC
Rango de velocidad [rpm]	5 - 280
Dirección reversible de la rotación	sí
Elevador	Motor
Movimiento [mm]	140
Rango de temperatura de calefacción [°C]	temp. ambiental - 180
Potencia de calefacción [W]	1350
Control de calentamiento preciso [K]	±1
Volumen max. de Baño [l]	4
Contador de tiempo	sí
Dimensiones (An x Al x Pr) [mm]	500 x 430 x 440
Peso [kg]	18.5
Temperatura ambiental permitida [°C]	5 - 40
Humedad relativa permitida [%]	80
Clase de protección de acuerdo al DIN EN 60529	IP 20
Interfaz de RS 232	sí
Voltaje [V]	220 - 240
Frecuencia [Hz]	50/60
Consumo de energía [W]	1400