

## SUPROL PRO

### Description

**SUPROL PRO** is a ready-for-use, waterless solution for the rinsing of disassembled and assembled clockworks after the cleaning in watch cleaning machines. The cleaning solution used before is thoroughly removed and **SUPROL PRO** evaporates without residue. Subsequent lubricants will be taken uniform by the rinsed surfaces.

**SUPROL PRO** is also suitable for rinsing and water replacement before the drying in the course of an aqueous cleaning and rinsing process for metallic precision parts. **SUPROL PRO** does not contain benzene and it is dearomatized.

### Application and Dosage

- Dosage: pure, ready-for-use • Rinsing time: about 3 min.
- If one of the Elma cleaning machines Elmasolvex VA, RM and SE as well as RM 90 or Superelite is used, at first clean the clockworks in WF PRO.
- Then rinse multiple with the rinsing solution **SUPROL PRO**.
- If a complete re-lubrication is required, use UNIMIX for the last rinsing step.

### Safety Recommendations

**SUPROL PRO** is classified as hazardous according to the Regulation (EC) No 1272/2008 [GHS] (flammable, eye irritation, narcotic effect, aspiration toxicity, hazardous to the aquatic environment - chronic category 3).

Observe also with respect to this the hints indicated in the safety data sheet and always handle chemicals with care.

### Physical-chemical characterisation

- Density: 0.74-0.77 g/ml.
- Flash point: 23-28 °C.
- **SUPROL PRO** is not miscible with water and keeps on top of water.
- Mixture of solvents, free of halogens like chlorine or fluorine.

### Disposal

Recommendation:

1. Disposal regulations same as for used oil/diesel/benzine.
2. Dispose via specialised disposal companies: European waste code: 14 06 03\*, „other solvents and solvent mixtures“.
3. Burn in suitable equipments, but according to official regulations.

Transport in appropriate suitable containers. Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Do not discharge product unmonitored into the environment.

### Volumes, Storage and Transport

- Available volumes: 2.5 l can [REF 8000440](#), 5 l can [REF 8000444](#), 10 l can [REF 8000441](#) and 30 l can [REF 8000443](#).
- Keep in tightly closed original container at a cool and ventilated place and protected from heat and direct solar radiation. Do not store together with oxidizing agents.
- Do not mix with other chemicals.
- Keep away from ignition sources.
- Shelf life: 3 years from date of production (see lot on label).
- Classification for all means of transport: class 3, UN 3295.

### Accessories

- Tap (outlet tap): for 2.5 l / 5 l / 10 l / 30 l can [REF 8000003928](#).
- Dosing cup: 250 ml vol./5 ml-scale [REF 8000643](#) • 1000 ml vol./10 ml-scale [REF 8000647](#).