

## Polypropylene Horizontal Air Flow Laminar Clean Bench - PRO

TopAir provides high-quality, safe Horizontal Laminar Clean Benches. Clean benches are designed to supply a clean controlled work environment meeting Class 100/ISO 5 Cleanliness level. The clean bench is tested according to USA Federal Standard 209E/ISO 14644-1/CE.

TopAir's clean benches draw air from the room or hall space, pass it through a HEPA filter using a fan, and then distribute the clean air across the bench area. In Horizontal benches, the filtered air is directed downwards through a filter installed at the back of the bench.

## Structure:

- 8 mm welded polypropylene with high chemical resistance
- stainless steel 304 worktop, (SS316 optional)
- 5 mm safety front glass window with counterweight system
  - Side windows for better visibility
- Optional Integrated Particle Monitoring System (IPMS)

- Microprocessor control system with 10.1" color touchscreen display
- Automatic speed control to maintain 0.33 m/s (66 fpm)
- Downflow alarms, critical "red light" chamber alarm, service alarm, filter alarm
- Real-time filter status gauge display
- High efficiency quiet EC fan
- Germicidal waterproof UV light (254 nm) system and safety interlock mechanism
- LED light 800 lux
- 2 x universal sockets
- Includes metal stand and casters
- Multi-language control with metric or Imperial units
- Compliance with US Federal Standard 209E / ISO 14644-1 / CE
- Optional Integrated particle monitoring system (IPMS)

The IPMS measures particle concentration in real-time, monitoring the cleanliness level 24/7. Its display clearly indicates whether or not the cleanliness level complies with ISO-5, and alerts when the workspace has been contaminated and needs to be serviced.

## **Red Light Alert:**

Whenever there is an air velocity failure, a red light inside the unit switches on, and the system automatically switches off. This enables convenient detection of failures from a distance, facilitating notice even for the hearing-impaired.



## Polypropylene Horizontal Air Flow Laminar Clean Bench - PRO

Spec/ Model	HC-H090-PRO	HC-H120-PRO	HC-H150-PRO	HC-H180-PRO
Outer Dimensions WxDxH	35.4*36.6*47.2" 900*930*1200 mm	47.2*36.6*47.2" 1200*930*1200 mm	59*36.6*47.2" 1500*930*1200 mm	70.8*36.6*47.2" 1800*930*1200 mm
WE CAN CUSTOMIZE ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS				
Workspace (W x D x H)	30.3*24.4*23.6" 770*620*600 mm	42.1*24.4*23.6" 1070*620*600 mm	53.9*24.4*23.6" 1370*620*600 mm	65.7*24.4*23.6" 1670*620*600 mm
Test Standard	USA Federal Standard 209E / ISO-14644-1, CE			
Air Velocity m/s	0.33 m/s, 66 fpm			
Cleanliness in Workstation	Class-100 (FS 209E) ISO-5, ISO-14644-1			
Hood Material	Polypropylene			
worktop Material	Stainless steel 304			
Noise Level (Tested 20 cm from worktop, 1.2m / 48" above ground)	<52dB	<54dB	<56dB	<56dB
Power Supply	110 / 220 V, 50/60 Hz, Single phase			
Illumination	800 lux LED lighting			
Filters	HEPA Filter Efficiency of 99.9995% at 0.3 microns H14 (Optional ULPA filter)			